



W1

Exhaust Clamp

This clamp was designed specifically for use in automotive applications as its name suggests.

It is used to join safely and securely two metal tubes subject to constant high temperatures and vibration, thereby avoiding leaks of exhaust fumes.

The edges of the clamp are rounded in order to avoid damage to the exhaust system. The exhaust clamp is easy to assemble and provides uniform clamping force around the circumference of the tube.

Exhaust Clamp W1

Article	Application Ø		Part n° W1	Mxb	S + 0,2	Box Quantity (MOQ)	Packing
	mm	inches					
ATE 30	27,0-30,0	1-1/16-1-3/16	03002765	M8x55	1,5	250	250
ATE 33	30,0-33,0	1-3/16-1-19/64	03002773	M8x55	1,5	250	250
ATE 36	33,0-36,0	1-19/64-1-27/64	03002781	M8x60	2,0	250	250
ATE 39	36,5-39,5	1-7/16-1-9/16	03002785	M8x65	2,0	250	250
ATE 42	39,0-42,0	1-17/32-1-21/32	03002790	M8x60	2,5	100	100
ATE 43	40,5-43,5	1-19/32-1-23/32	03002791	M8x65	2,5	100	100
ATE 45	42,0-45,0	1-21/32-1-49/64	03002802	M8x65	2,5	100	100
ATE 48	45,0-48,0	1-49/64-1-57/64	03002810	M8x80	2,5	100	100
ATE 50	47,5-50,0	1-7/8-1-31/32	03002829	M8x60	2,5	100	100
ATE 51	48,0-51,0	1-57/64-2-1/64	03002837	M8x60	2,5	50	50
ATE 52	49,0-52,0	1-59/64-2-3/64	03002845	M8x65	2,5	50	50
ATE 54	52,0-54,1	2-3/64-2-1/8	03002853	M8x65	2,5	50	50
ATE 56	53,0-56,0	2-3/32-2-13/64	03002861	M8x65	2,5	50	50
ATE 58	55,0-58,0	2-11/64-2-9/32	03002870	M8x70	2,5	50	50
ATE 59	57,0-59,1	2-1/4-2-21/64	03002888	M8x70	2,5	50	50
ATE 61	58,0-61,0	2-9/32-2-13/32	03002896	M8x80	2,5	50	50
ATE 64	61,0-64,0	2-13/32-2-33/64	03002909	M8x80	2,5	50	50
ATE 71	67,0-71,0	2-41/64-2-51/64	03002917	M10x90	3,0	50	50

W1 Bolt: 8.8 grade steel white zinc-plated **Band:** St34 (DIN 2393C) Steel

