



W4

Stainless Steel Double Bridge Clip

The Double Bridge clip was developed by the Mikalor R&D Department due to requirements from the ventilation sector and also for applications involving fume, woodchip and dust extraction for a clamp suitable for spiral hose incorporating an outer helix.

This is just one example of how we put our engineering know-how at the service of our customers. We work together with our customers to design and craft the solution to their needs in each case. The Double-Bridge clip is manufactured in AISI-304 stainless steel.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling. **Patented Worldwide.**

* Also available in **W2**, **W3** and **W5** on request.

* This clamp can also be supplied with a single bridge.

ASFA "L" W4 Double Bridge Clip (9mm bandwidth)

Application Ø		a+0,3 a-0,2	S + 0,10	b Max.	L	h	Box Quantity (MOQ)	Packing
mm	inches							
50-70	1-31/32-2-3/4	9	0,65	14	25,6	10	100	100
60-80	2-23/64-3-5/32	9	0,65	14	25,6	10	100	100
70-90	2-3/4-3-35/64	9	0,65	14	25,6	10	100	100
80-100	3-5/32-3-15/16	9	0,65	14	25,6	10	50	50
100-120	3-15/16-4-23/32	9	0,65	14	25,6	10	25	50
120-140	4-23/32-5-33/64	9	0,65	14	25,6	10	25	50
140-160	5-33/64-6-19/64	9	0,65	14	25,6	10	25	50

ASFA "S" W4 Double Bridge Clip (12mm bandwidth)

Application Ø		a+0,3 a-0,2	S + 0,10	b Max.	L	h	Box Quantity (MOQ)	Packing
mm	inches							
150-170	5-29/32-6-11/16	12,2	0,8	18	34,6	11	100	100
150-170	5-29/32-6-11/16	12,2	0,8	18	34,6	11	25	25
160-180	6-5/16-7-3/32	12,2	0,8	18	34,6	11	25	25
170-190	6-11/16-7-15/32	12,2	0,8	18	34,6	11	10	10
180-200	7-3/32-7-7/8	12,2	0,8	18	34,6	11	10	10
190-210	7-31/64-8-17/64	12,2	0,8	18	34,6	11	10	10
200-220	7-7/8-8-21/32	12,2	0,8	18	34,6	11	10	10
210-230	8-17/64-9-1/16	12,2	0,8	18	34,6	11	10	10
220-240	8-21/32-9-9/64	12,2	0,8	18	34,6	11	10	10

W4 Screw: Stainless steel (AISI-304) Cu (A2) **Band and Housing:** X5CrNi 1810 Stainless steel (DIN 1.4301) (AISI-304) (A2)

